



Specialty Flooring Products

www.nikkacorp.com | (678) 290-0830

BIO CLEAN 900

BIO CLEAN 900 is a heavy-duty cleaner formulated for versatility and dependability. Its uses can encompass anything from floor cleaning to hot dip tank cleaning. Worker safety is an integral part of the manufacturing process and this product contains no caustics, butyl ethers, or chlorinated and petroleum-based solvents. Unlike many industrial strength cleaners, Bio Clean 900 is 100% biodegradable and environmentally safe. The versatility of this product is enhanced by complete water reducibility to assure the capability to customize the cleaning strength to meet your specific needs. Bio Clean 900 is a concentrated non-flammable detergent that dissolves a wide range of greases and oil based soils while leaving the area with a refreshing citrus scent. Terpene hydrocarbons, the major component of oranges, and naturally occurring, are used in this product. As a water reducible cleaner, the ability to work with and around most metals is assured by the addition of flash rust additives and inhibitors. This product is compatible with most industrial coatings including epoxies and urethanes

RECOMMENDED FOR:

Restaurants, Hotels, Kitchens, Bathrooms, Trucking Fleets, Mills, Manufacturing plants, Contract Cleaning Firms, Governmental Buildings, Waste Clean up, Military Institutions, Schools

BENEFITS:

Biodegradable, Environmentally Safe, No caustics, butyl esters, chlorinated or petroleum-based solvents
Nonflammable, Concentrated Formula, Safe for most Epoxy & Urethane Floors

DIRECTIONS FOR USE:

For heavy duty cleaning and degreasing, we recommend 1 part Bio Clean 900 to 4 parts water by volume. Deviations from this ratio can employ differing concentrations suited to the cleaning strength needed. For less soiled floors, dilute with more water and for heavily soiled floors, dilute with less water. Ratios varying from 1:1 to 50:1 (Water: Bio Clean 900) can be used for cleaning.

APPLICATION PROCEDURE:

For cleaning- dilute Bio Clean 900 to the desired strength and apply to the surface with a mopping action. Allow the solution to remain on the floor for approximately five minutes. Remove the loosened grime and dirt by mopping and then rinse the floor with clean water. For walls, woodwork, and enameled surfaces, apply the diluted Bio Clean 900 directly by a sponge of cloth. Rinse the surface with a clean water dampened cloth or sponge. Always check product compatibility before using.

Warranty

Since no control is exercised over product use, The Nikka Corporation warrants that its products are manufactured free from defect and are consistent and within manufacturing tolerances on our data sheets. No other oral or written representation or statement of any kind, expressed or implied, now or hereafter made is authorized or warranted by The Nikka Corporation. This product is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular use. The Nikka Corporation shall have no liability for incidental or consequential damage, direct or indirect. Our liability is limited to price of or replacement of our product at our option. By accepting delivery of our product means that you have accepted the terms of The Nikka Corporation Warranty

NIKKA CORPORATION
1880 WEST OAK PKWY STE 110
MARIETTA, GA 30062
678-290-0838
WWW.NIKKACORP.COM