

EARTHTONE CONCRETE STAIN DOUBLE STRENGTH INORGANIC ACID BASED STAINS



EARTHTONE CONCRETE STAIN IS A DEEP PENETRATING PERMANENT CONCENTRATED STAIN THAT IS UV STABLE WHEN SEALED. THIS PRODUCT WILL NOT FADE IN DIRECT SUNLIGHT. IT IS IDEAL FOR INTERIOR OR EXTERIOR APPLICATIONS. CONTAINS NO VOCS.

PRODUCT HIGHLIGHTS

• **UV stable:** Once dry and sealed, Earthtone Concrete Stains remain stable and resistant to weather and sun light for years.

• A wide range of colors: Earthtone Concrete Stains at various dilutions and combinations can offer a multitude of colors and shades for any desired effect in beautifying plain concrete surfaces.

• Ease of application: Earthtone Concrete Stains do not require any neutralizing or labor intensive scrubbing. Once dry they can simply be rinsed thoroughly and when dry again, apply the sealer. A third of the labor is eliminated.

• Economical: The colors cover 250 Sq. Ft./gal and many can be diluted to provide even more economical coverage.

• Long shelf life: Earthtone Concrete Stains can be stored in the original bottle for up to one year with no loss of activity.

USES

The Earthtone Concrete Stains are applied to any clean, cured concrete surface or concrete overlay surface and allowed to react and dry. Once washed and sealed, the various colors that are applied become a permanent part of the concrete with lasting beauty.

Earthtone Concrete Stains are perfect for interior applications such as garage floors, basements, showrooms and living areas, as well as outdoor applications such as patios, sidewalks, pool decks, driveways and concrete surfaces where mottling and antiquing are wanted.

Earthtone stains are permanent because they chemically react with the concrete.

QUICK LOOK:

Type : Reactive acid based concrete stains Toxicity: Harmful if swallowed VOC's: None Flammability: Non-flammable Composition: Various metallic entities in an aqueous acidic base Color: Various Odor: Slight pungent Coverage: 250-400 Sq. Ft. per gallon *Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided. FOR MORE INFORMATION, PLEASE SEE SDS.



*Product warranty for one year from date of manufacture For more information on EZChem USA and all products manufactured by EZChem please visit our website: www.ezchemusa.com



EARTHTONE CONCRETE STAIN

HOW TO USE:

1. Clean concrete with Super Blue to remove dirt or stains, and CitraPro to remove any oily deposits. Be sure that the surface is free of any sealants or coatings.

2. Apply stain with acid brush, sponge, or plastic sprayer in the color and technique of your choice.

3. Allow to dry thoroughly. Drying time will vary according to surface conditions and humidity. Next, wash or damp wipe residue from surface.

4. Allow to completely dry again(usually at least 24 hours), and apply sealer to enrich and protect your finished project.

5. PermaPro EZGIo Floor Polish is strongly recommended on indoor applications to protect and keep your floor looking new.

CLEAN UP:

Discard brush or application utensil in an appropriate manner, or clean thoroughly with soap and water.

PRECAUTIONARY STATEMENT:

Do not breathe dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/ face protection. Take off contaminated clothing and wash before reuse. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

IF INHALED: Move to fresh air immediately. If breathing difficulty continues, Get Medical Help.

IF IN EYES: Flood with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical attention.

IF SWALLOWED: Do not induce vomiting. Drink two glasses of water and Get Medical Help Immediately.

IF ON SKIN: Wash with soap and water. Remove contaminated clothing and launder before reuse. If irritation develops, Get Medical Help

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP 24 Hours a Day contact: INFOTRAC at 1-800-535-5053

