



# COLOR RELEASE AGENT



## POWDER RELEASE AGENT

**COLOR RELEASE AGENT IS A PIGMENTED, READY TO USE POWDER RELEASE AGENT THAT IS BROADCAST OR DUSTED ONTO THE SURFACE OF FRESH CONCRETE TO PREVENT STAMPING AND TEXTURING TOOLS FROM STICKING TO THE CONCRETE SURFACE DURING THE IMPRINTING PROCESS.**

### PRODUCT HIGHLIGHTS

- Color release agent can be used on both integrally colored concrete and/or together with Color Hardener.
- Packaged in 30lb pail

### QUICK LOOK:

Type :  
Toxicity:  
VOC's:  
Flammability: Non-flammable  
Composition:  
Odor:  
Coverage: 100 sq.ft. per 3-4lbs  
*\*Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,  
PLEASE SEE SDS.



### USES

Color Release Agent is a pigmented, ready to use powder release agent that is broadcast or dusted onto the surface of fresh concrete to prevent stamping and texturing tools from sticking to the concrete surface during the imprinting process.

When the concrete hardens sufficiently, the surface is washed to remove most of the Color Release Agent material.

Some of the Color Release Agent remains in the creases and impressions of the concrete to create color accents, random mottling effects or to contrast with the underlying color of the concrete surface.



# COLOR RELEASE AGENT

## **HOW TO USE:**

**INSTALLATION:** Color Release Agent is sprinkled or spread (broadcast) onto fresh concrete with a masons brush after troweling or finishing operations are complete, but prior to starting stamping or embossing procedures.

**COMPOSITION:** Color Release Agent is a powder blend of concentrated color pigments milled together with surface conditioners and lubricating agents.

**COLOR & FINISHES:** Antique Release is available in 25 standard colors and plain. Two or more Color Release Agent colors can be used in combination to create different patterns or contrasting effects. Typically a dark shade of Color Release Agent is applied over a light shade of Color Hardener or colored concrete to create a contrasting effect.

**LIMITATIONS:** Color Release Agent must be applied to freshly-placed concrete before the concrete hardens. It is not designed to permanently bond to the concrete surface. Surface appearance may vary depending on application technique, finishing method, weather conditions, curing and sealing methods and the preparation and composition of the concrete mix material

## **PRECAUTIONARY STATEMENT:**

Avoid breathing dust/fume/gas/mist/vapors/spray. Wash hands thoroughly after handling. Use respirators. Store in a well-ventilated place. Keep container tightly closed. Dispose of contents/ container according to local, state and federal regulations.

## **FIRST AID:**

**EYE CONTACT:** Flush eyes with plenty of water for at least 15 minutes using fingers to hold eyelids open. Seek Medical Attention.

**SKIN CONTACT:** Wash with soap and water. Remove contaminated clothing.

**INHALATION:** If discomfort persists, get medical attention.

**INGESTION:** Do not induce vomiting. Seek immediate medical attention.

## **IN CASE OF FIRE:**

This product is not flammable.

## **FOR EMERGENCY HELP**

**24 Hours a Day contact:**

**INFOTRAC at 1-800-535-5053**