



STAMP MIX



SINGLE COMPONENT CEMENTICIOUS OVERLAY

STAMP MIX IS A READY TO USE, ONE COMPONENT OVERLAY SYSTEM THAT BONDS TO ALL CLEAN CONCRETE SURFACES TO PRODUCE A ROCK HARD, WEATHER PROOF SURFACE. IT CAN BE TROWELED OR STAMPED, STAINED AND SEALED FOR A BEAUTIFUL, LONG LIFE FLOOR.

PRODUCT HIGHLIGHTS

- **One component mix:** No extra additives. Just add water, mix and apply. Saves time and money.
- **Repairs and resurfaces** old and worn concrete.
- **Replicates stamps** with a sharp well defined image that is superior to all other stamp mixes.
- **Rock hard surface:** Stamp Mix sets to a superior, rock hard surface that resists water penetration and re-wetting. This means beauty that lasts.
- **Stains fast and easy:** Although the surface is rock hard, it will take acid stains or water based stains with equal ease. Properly sealed this is a low maintenance surface that is easy to keep clean.
- Interior surfaces coated with EZ GLO™ acrylic polish over the initial seal coat can be maintained for years and never need resealing.
- **Packaged in 50lb bags**
- **Available in white or grey**

USES

Stamp Mix is used to restore and beautify commercial and residential areas such as patios, walk ways, pool decks, driveways, interior basement rooms, bath rooms and kitchens. It resurfaces and restores all concrete surfaces with one simple application.

QUICK LOOK:

Type : Single component cementitious overlay system

Toxicity: Low. Alkaline mixture. Harmful if swallowed.

VOC's: Zero

Flammability: Non-flammable

Composition: Portlant cement, sand and proprietary additives.

Odor: N/A

Coverage: 15sq.ft. @ 3/8inch • 20-23sq.ft. @ 1/4inch

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

Application Temperature:

Cured:

FOR MORE INFORMATION,
PLEASE SEE SDS.





STAMP MIX

PRIME/BOND COAT:

The surface must be clean and free of any dirt or debris. Just prior to applying Stamp Mix the substrate must be primed with Bond It primer. Do not allow Bond It primer to dry completely. Stamp Mix must be applied over wet Bond It.

MIXING INSTRUCTIONS:

One 50 pound bag of Stamp Mix will require approximately 5.5 quarts (minimum 4.5 maximum 6.5) of water. For best results use a 1/2 inch drill with a Jiffy type mixing paddle. Add the measured water to a clean 5 - gallon pail. Add one EZ-Color Pak pigment pack to your measured water and mix in. With the mixer running, slowly add the Stamp Mix powder, mixing until a lump free consistency is obtained. Allow the mixed material to set, or slake for approximately 5 minutes and then re-mix prior to placement. Mix only the amount of material that can be placed within 30 minutes of mixing. Keep bagged material and mixed material out of direct sunlight for added work time. Use cold water when mixing for added working time. In cooler conditions, use warm water when mixing. Consult product technical data sheet for surface preparation and installation.

PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconscious person.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053